

ATF DEXRON III



Data sheet

A automatic transmission fluid.

APPLICATIONS

- Transmission fluid meeting the General Motors as **DEXRON® IIIG** intended for most automatic transmissions of recent designs.
- Automatic and power-shift transmission and torque converters of passenger cars, light commercial vehicles and industrial vehicles.
- Hydraulic systems where a fluid of type GM DEXRON® III is required.

PERFORMANCES

OEMs Specifications

Meet the requirements of followings:

- GM DEXRON®-IIIG
- Ford MERCON®
- Allison C-4
- Caterpillar TO-2

CUSTOMER BENEFITS

- Outstanding resistance to corrosion, foaming, shearing and rust formation.
- High degree of anti-wear and extreme pressure properties
- Outstanding friction and heat transfer properties
- Perfect behaviour at low temperature
- Proven compatibility with elastomers (seals)
- Superior oxidation resistance

CHARACTERISTICS

ATF DEXRON III	Units	
Volumetric mass at 15°C	Kg/m ³	853
Colour, ASTM	-	Red
Kinematic Viscosity at 40°C	mm ² /s	34.08
Kinematic Viscosity at 100°C	mm ² /s	7.19
Kinematic Viscosity at -40°C index	mPa.s	10200
Viscosity Index		180
Flash point Cleveland	°C	202
Pour Point	°C	-45

The typical characteristics represent mean values.

ATF DEXRON III
31 January 2005

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.