

# TRANSMISSION TM 85W-140



## GEAR OIL

### USES

- Gear boxes, axles, transfer boxes.
- Specially recommended for highly loaded hypoid gears.
- All types of gears when the MIL-L-2105D specification or API GL-5 is required.

### PROPERTIES

- High viscosity index.
- High Extreme-Pressure properties.
- Excellent antifoam, anticorrosive and antirust properties.
- Excellent stability in operation.

### CHARACTERISTICS

TRANSMISSION TM	Units	Grade SAE 85W-140
Volumetric mass at 15°C	kg/m <sup>3</sup>	910
Viscosity at 40°C	mm <sup>2</sup> /s	345
Viscosity at 100°C	mm <sup>2</sup> /s	25
Viscosity index	-	92
Flash point Cleveland	°C	228
Pour point	°C	-15

*The typical characteristics mentioned represent mean values.*

### SPECIFICATIONS

API GL-5

TOTAL LUBRIFIANTS  
16, rue de la République  
92800 PUTEAUX

TRANSMISSION TM 85W-140  
JULY 2005  
N° MPR 07/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant